





1. TANK IS DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH U.N. SPECIFICATIONS
2. TANK IS AIR TESTED AT 3 PSI
3. ALL WELDS CLEANED OF SLAG AND SPATTER
4. TANK INTERIOR AND EXTERIOR ARE ELECTRO-CLEANED
5. DRUM LID TO BE INSTALLED BY: STRIKE RING AROUND CIRCUMFERENCE WITH A MALLET THEN TIGHTEN THE BOLT WITH A WRENCH. REPEAT UNTIL BOLT TIGHTENING RESISTANCE DOES NOT CHANGE (REF: 40 LB-FT)
6. 2IN BUNG TO BE INSTALLED 3/8 TO 1/2 ROTATION BEYOND SOLID GASKET CONTACT (REF: 30 LB-FT)

BILL OF MATERIALS



LINCOLN, NE 68504 PHONE:(402) 467-5221 FAX:(402) 467-3247

	CUSTOMER
--	----------

SII STANDARD

JOB:

6984400B51303

SCALE: 1:10

APPROVED BY:

DRAWN BY: JCB

DATE:	10/
DESCRIPTION:	

DRAWING NUMBER:

446

446 GAL 42 X 48 SUPERTAINER SS

18225e